UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/523,141	01/31/2005	Suk-Won Chun	11281-065-999	1407

20583 7590 02/09/2007

JONES DAY
222 EAST 41ST ST
NEW YORK, NY 10017

EXAMINER	
EWALD, MARIA VERONICA	
ART UNIT	PAPER NUMBER
1722	

SHORTENED STATUTORY PERIOD OF RESPONSE	MAIL DATE	DELIVERY MODE
3 MONTHS	02/09/2007	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

If NO period for reply is specified above, the maximum statutory period will apply and will expire 6 MONTHS from the mailing date of this communication.

Office Action Summary	Application No.	Applicant(s)	
	10/523,141	CHUN ET AL.	
	Examiner	Art Unit	
	Maria Veronica D. Ewald	1722	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

1)☐ Responsive to communication(s) filed on _____.

2a)☐ This action is **FINAL**. 2b)☒ This action is non-final.

3)☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

4)☒ Claim(s) *1-22* is/are pending in the application.

4a) Of the above claim(s) _____ is/are withdrawn from consideration.

5)☐ Claim(s) _____ is/are allowed.

6)☒ Claim(s) *1-22* is/are rejected.

7)☐ Claim(s) _____ is/are objected to.

8)☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

9)☐ The specification is objected to by the Examiner.

10)☒ The drawing(s) filed on *31 January 2005* is/are: a)☒ accepted or b)☐ objected to by the Examiner.

Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).

Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).

11)☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

12)☒ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).

a)☒ All b)☐ Some * c)☐ None of:

1.☒ Certified copies of the priority documents have been received.

2.☐ Certified copies of the priority documents have been received in Application No. _____.

3.☒ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

1) ☒ Notice of References Cited (PTO-892)
2) ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)
3) ☒ Information Disclosure Statement(s) (PTO/SB/08) Paper No(s)/Mail Date *1/31/05*.
4) ☐ Interview Summary (PTO-413) Paper No(s)/Mail Date. _____ .
5) ☐ Notice of Informal Patent Application
6) ☐ Other: _____.

DETAILED ACTION

Claim Rejections - 35 USC § 112

13. The following is a quotation of the second paragraph of 35 U.S.C. 112:

> The specification shall conclude with one or more claims particularly pointing out and distinctly claiming the subject matter, which the applicant regards as his invention.

Claim 17 is rejected under 35 U.S.C. 112, second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter which applicant regards as the invention. As written, claim 17 recites the limitation "the body frame" in line 2; however there is no previous mention of “a body frame” only “a body.” Thus, there is insufficient antecedent basis for this limitation in the claim. Claim 17 requires clarification and/or correction.

Claim Rejections - 35 USC § 102

14. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

> A person shall be entitled to a patent unless –
>
> (e) the invention was described in (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent or (2) a patent granted on an application for patent by another filed in the United States before the invention by the applicant for patent, except that an international application filed under the treaty defined in section 351(a) shall have the effects for purposes of this subsection of an application filed in the United States only if the international application designated the United States and was published under Article 21(2) of such treaty in the English language.

Claims 1 – 5 are rejected under 35 U.S.C. 102(e) as being anticipated by Haynes, et al. (U.S. 6,709,623). Haynes, et al. teach an apparatus for producing nanofiber utilizing electrospinning comprising: a supply unit for supplying polymer

materials of the liquid state used to produce fibers (column 7, lines 18 – 20); a spinning unit having a plurality of spinning nozzles (item 10 – figure 1) for discharging the polymer materials supplied by the supply unit in a charged filament form (column 7, lines 18 – 27); a collector installed below the spinning unit for piling the charged filament discharged by the spinning unit in a specific thickness (item 26 – figure 1; column 7, lines 28 – 30); and a control unit charged to have a voltage of same polarity as one of the charged filament and positioned between the spinning unit and the collector for guiding the stream of the charged filament in order to prevent repulsion and dispersion of the charged filaments discharged from each spinning nozzle (item 24 – figure 1; column 7, lines 28 – 30, 63 – 67; column 8, lines 1 – 10); wherein there is an induction unit positioned between the control unit and the collector to surround the filament stream for inducing the charged filament stream passing through the control unit toward the collector, a voltage of same polarity as the control unit being applied to the induction unit (item 15 – figure 1); wherein there is a transfer mount for reciprocating the spinning unit at a predetermined speed (column 7, lines 20 – 30); wherein there is an air conditioning unit for inhaling air into an air layer between the spinning unit and the collector and discharging a solvent from the air layer to the outside (item 30 – figure 1; column 7, lines 30 – 35); wherein the spinning unit includes at least one spinning nozzle pack in which the spinning nozzles are arranged in series (item 10 – figure 1).

Claims 11, 14, 17 and 19 are rejected under 35 U.S.C. 102(e) as being anticipated by Kim (U.S. 6,991,702). Kim teach a spinning nozzle pack for forming a

polymer web by electrostatically spinning a solution used as a fiber-forming material, comprising: a body having a supplier for supplying the solution (item 1 – figure 1) and a received for receiving the supplied solution (item 3 – figure 1); an electric connector mounted on the body to be sunk in the solution for charging the solution when voltage is supplied thereto (item 5 – figure 1; column 2, lines 40 – 47); and a plurality of spinning nozzles, each having a capillary tube for discharging the solution charged by the electric connector in fine filament form (item 4 – figure 1; column 2, lines 40 – 47); wherein the electric connector is made in a shape of a conductor board or conductor stick of a predetermined length and has valleys and ridges periodically formed along a longitudinal direction thereof, and wherein the ridges are fit on the center of the spinning nozzles (item 5 – figure 1; column 2, lines 44 – 47); wherein the spinning nozzle can be combined in an orifice of the body frame selectively (figure 1; column 3, lines 5 – 15); wherein the capillary tube is integrally formed with the body (figure 1; column 3, lines 5 – 15).

Claim Rejections - 35 USC § 103

15. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

> (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.

Claims 6, 12, 18, 21 and 22 are rejected under 35 U.S.C. 103(a) as being unpatentable over either Haynes, et al. or Kim in view of James, et al. (U.S. 7,018,188).

Kim and Haynes, et al. teach the characteristics previously described but do not teach that the nozzles have gradually shorter lengths outward from the center nor teach the diameter sizes or material of the tubes.

In a method to form nanofibers, James, et al. teach a spin pack with a plurality of nozzles. The nozzles can have varied configurations. For example, the reference teaches that the nozzles can be of varying lengths, with gradually shorter lengths on the outer nozzles (figure 4a). The nozzles can extend away from the supply cavity in different amounts; some nozzles may extend beyond the cover plate (item 60 – figure 4a). James, et al. teach that there is a non-linear relationship between the nozzle extension relative to the downstream surface of the cover plate and the effect on fiber characteristics (column 9, lines 1 – 10). Thus, configuring a spin pack, such that the outermost nozzles are shorter in length may be desirable depending on the fiber characteristics that the user specifies. In addition, James, et al. teach that optimum inner and outer diameter dimensions for the tube are approximately 0.25 mm and 0.81 mm, respectively with a total length of 31.8 mm. All dimensions are within the range of 0.05 – 2 mm (inner diameter); 0.1 – 4 mm (outer diameter); 0.5 – 50 mm (length). Furthermore, the material of the nozzle pack can be metal (column 7, lines 14 – 15). In addition, the reference further teaches that there is a supply cavity (item 25 – figure 1), which is covered and connected to the spin pack assembly.

Therefore, it would have been obvious to one of ordinary skill in the art at the time of the Applicant's invention to configure the apparatus of either Kim or Haynes, et al. such that the nozzle lengths are gradually shorter at the outermost ends, with the

dimensions and spin pack configuration of James, et al. for the purpose of producing filaments with varying characteristics, depending on specific requirements by the user.

Claims 7 – 10 are rejected under 35 U.S.C. 103(a) as being unpatentable over Haynes, et al. Haynes, et al. teaches the characteristics previously described but do not teach that the distance between the control unit nor teach the speeds of the collector unit. Haynes, et al., however, do teach that there is a carrier unit for carrying a piling material to which the filament adheres and is discharged to the collector (column 7, lines 25 – 35).

The distance between the control unit and spinning nozzle, the speed of the conveyor belt and the rotating drum are considered result-effective variables and can be optimized through routine experimentation. See In re Boesch, 617 F.2d 272, 205 USPQ 215 (CCPA 1980).

Therefore, it would have been obvious to one of ordinary skill in the art at the time of the Applicant's invention to configure the distance of the control unit from the nozzle, or the speed of the collector unit at the ranges specified by the Applicant, depending on the optimum characteristics of the filaments desired, such as thickness and ply of the finished web.

Claim 13 is rejected under 35 U.S.C. 103(a) as being unpatentable over Kim in view of Kaun (U.S. 5,435,708). Kim teach the characteristics previously described but

do not teach that the body of the nozzle pack is made of engineering plastic, though it is known that the nozzle pack and its body can be made of any suitable material.

For example, in a method to produce filament fibers, Kaun teaches that there is a nozzle head comprised of a bar-shaped horizontal plastic nozzle or spinneret (column 4, lines 3 – 5). The nozzle is further comprised of at least one row of orifices or openings, through which filaments are discharged (column 4, lines 5 – 9).

Therefore, it would have been obvious to one of ordinary skill in the art at the time of the Applicant's invention to configure the spin pack body of Kim with a plastic body, as configured by Kaun, if so desired by the user, when producing the filament fibers.

Claims 15 – 16 are rejected under 35 U.S.C. 103(a) as being unpatentable over Kim in view of Wnuk, et al. (U.S. 6,604,928). Kim teaches the characteristics previously described but do not explicitly teach the presence of a filter prior to discharging the solution to the spinning nozzles. However, it is known to one of ordinary skill in the art to include a filter assembly with melt-spinning of fibers, since the polymer melt must be subjected to a super-fine filtration before passage to the spinneret plate (Wnuk, et al.; column 1, lines 18 – 20).

In a method to produce filaments via a spinneret, Wnuk, et al. teach that a polymer solution flows through a housing; prior to discharge to the spinning head (item 10 – figure 1), the solution flows through a filter element (item 18 – figure 1) which is comprised of filtering material (item 20 – figure 1). The filtering material is comprised

preferably of a pleated filter cover of wire gauze or of a metallic non-woven fabric, especially in the form of high-quality steel (column 4, lines 20 – 25). In addition, prior to discharge to each nozzle and subsequent to filtering, the polymer solution passes through a distribution device (item 22 – figure 1). The filter element surrounds the distribution device, such that polymer flows radially from the exterior, inward, passing through the filter element, into the distribution device and to the spinneret (column 3, lines 65 – 67; column 5, lines 8 – 19).

Therefore, it would have been obvious to one of ordinary skill in the art at the time of the Applicant's invention to configure the spin pack of Kim with the filter and distributor of Wnuk, et al. for the purpose of filtering the polymer solution prior to discharge to the spinneret.

Claim 20 is rejected under 35 U.S.C. 103(a) as being unpatentable over Kim in view of James, et al. and further in view of Lu (U.S. 6,183,684). Kim teaches the characteristics previously but does not teach that the capillary tubes are angled between 3 to 60 degrees so as to have a shape of a circular cone. However, the capillary tubes, as taught by, James, et al. can be of several shapes, depending on the requirements specified by the user – for example, the capillary tubes can be generally circular or may be tapered to look like a cone, such that the downstream effective diameter is less than the upstream effective diameter (column 7, lines 14 – 20).

In a method to form filaments, Lu teaches the use of a spin pack or drawing unit (item 31 – figure 2), in which the upstream portion of the capillary tubes are greater and

angled to be cone-shaped and decreasing in diameter towards the downstream or nozzle end (figure 2). The angle of the upstream portion is substantially between 15° to 60°, preferably between 30° to 45° (column 9, lines 35 – 40).

Therefore, it would have been obvious to one of ordinary skill in the art at the time of the Applicant's invention to configure the spin pack of Kim with the cone-shaped capillary tubes of Lu for the purpose of producing the desired filament characteristics and based on the requirements as specified by the user.

Conclusion

16. Any inquiry concerning this communication or earlier communications from the examiner should be directed to Maria Veronica D. Ewald whose telephone number is 571-272-8519. The examiner can normally be reached on M-F, 8 - 4:30.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Dr. Yogendra Gupta can be reached on 571-272-1316. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

MVE

YOGENDRA N. GUPTA
SUPERVISORY PATENT EXAMINER
TECHNOLOGY CENTER 1700